



ARVIA TMK002

TOUCH SCREEN MONITOR KIOSK

The Touchscreen Kiosk (Horizontal design) is perfect for retail, showroom, shopping mall, lobbies and many more place. It can be attract people to do something at your kiosk. The integrated, powerful operating system offers users exciting capabilities to deliver rich, engaging content with minimal operational burden required. Beyond a potential for sales and engagement, businesses also benefit from the reduced total operational costs that come with a low-maintenance, hassle-free visual display upgrade.

Key Features

- HD** LED Backlight
- LIFE** 50000 Hours Lifetime
- Super Slim Round Corner
- OS** Windows / Android
- 10 Points Capacitive Touch
- 7x24 Working Usage
- Tempered Glass on Surface
- Strong Anti-interference
- Fast Response
- LAN+WIFI Network

SPECIFICATIONS

| | | |
|-----------------------------------|--|---|
| Technical Parameter for LCD Panel | Panel Size | 24"-65" real color LCD screen |
| | Aspect Ratio | 16:9 |
| | Max. Resolution | 1920x 1080 |
| | Dot Pitch | 0.74mm(H) x 0.74mm(W) |
| | Number of Color | 16.7M |
| | Brightness | 450cd/m2 |
| | Contrast Ratio | 3000:1 |
| | Touch Technology | Infrared, Touch Foil & Capasitive |
| | Responsive Time | 5ms |
| Panel Life | above 50000 hours (Warranty 1 year) | |
| Media Player | OS | Android 6 |
| | CPU | RK3288, eight-core ARM Cortex A7 2.0 GHz Upgradeable to RK3366 |
| | GPU | ARM Mail-764 / Intel HD Graphics |
| | RAM | DDR 2GB (Upgradable to 4GB) |
| | Built-in storage capacity | 16GB SD, Support up to 32GB |
| | WIFI | WIFI module+WIFI Antenna + RJ45 Black&White |
| Supported files | Video formats | MP4(AVI:DIVX/XVID),MPG2(DVD:VOB/MPG2), MPEG1 (VCD: DAT/MPG1) |
| | Audio formats | MP3, WMA |
| | Photo formats | JPG,PNG,BMP |
| | Scrolling Text | ROL(UNICODE) |
| | Input/output interface | USB,RJ45 |
| Main Hardware | Shell Material | 100mm x 100m Casing : Plastic |
| | Surface | Metal case with powder burning; Tempered glass to protect LCD panel |
| | Speaker | 2*10W built-in stereo speakers |
| | Heat Dispersion | Built-in DC fans |
| Power | Standby | ≤3W |
| | Working | 30W-180W |
| | Power supply | AC 110V - 240V, 50/60HZ |
| Temperature | Storage | -7 to 65 Celsius degree |
| | Normal Working | -5 to 65 Celsius degree |
| OSD Language | English, Chinese, French, German, Italian, Spanish, Arabic | |



Israk Solutions Sdn. Bhd (1289622-T)

No. 20, Jalan BP 6/13, Bandar Bukit Puchong, 47120, Puchong, Selangor



<http://www.israk.my>



info@israk.my



03-8966 2405